Method for developing photographic silver halide recording materials.

Method for developing photographic silver halide recording materials.

Patent Number:

EP0429973

Publication date:

1991-06-05

Inventor(s):

KIESSLICH GUENTER DR (DE); WADEWITZ GUENTER (DE)

Applicant(s):

DU PONT DEUTSCHLAND (DE)

Requested Patent:

DE3938573

Application Number: EP19900121873 19901115

Priority Number(s): DE19893938573 19891121

IPC Classification:

G03C1/38: G03C5/305

EC Classification:

G03C1/38F, G03C5/305B

EC Classification:

G03C1/38F; G03C5/305B

Equivalents:

CA2029945.

JP3211546

Cited Documents:

US3754924; US2000353; US4840881; US4859567

Abstract

If photographic silver halide materials which contain nonionic fluorinated surface-active substances are developed in developers rich in hydroquinone and sulphite, the recorded image is spoilt by white spots. This defect disappears if a wetting agent is dissolved in a quantity of at least 0.1 g/l in the developer. The invention can be used in the production of images by means of silver halide materials, especially in medical diagnostics and in reprography.

Data supplied from the esp@cenet database - I2

Color developing solution for light-sensitive silver halide color bodiem odlesecore bas Isheram oldesecord

Color developing solution for light-sensitive silver halide color photographic material and processing method

Patent Number:

EP0436947

Publication date: 1991-07-17

Inventor(s):

UEDA YUTAKA C O KONICA CORPORA (JP); KOBOSHI SHIGEHARU C O

KONICA C (JP)

Applicant(s):

KONISHIROKU PHOTO IND (JP)

Requested

Patent:

EP0436947, B1

Application

Number:

EP19900125712 19901228

Priority Number(s):

JP19900158057 19900615; JP19890341357 19891228

IPC

Classification:

G03C7/413

EC Classification: G03C7/413

EC Classification: G03C7/413

Equivalents:

DE69031026D, DE69031026T, JP2915095B2.

Cited

US4232112; EP0312984; EP0273986; GB669505; FR1080765; US3996054;

Documents:

GB1094826; JP55018675; JP62056961

Abstract

There are disclosed a color developing solution for a light-sensitive silver halide color photographic material which comprises a sulfite concentration of 1.0 x 10<-><3> mole or lower per liter of the color developing solution and containing 0.5 to 20 g/l of a water-soluble surfactant and a processing method using the color developing solution.

Data supplied from the esp@cenet database - I2